

Via A. Volta 2 NOVENTA DI PIAVE
Venezia, VENETO 30020 ITALY
Tel: +39 0421 65191 / Fax: +39 0421 658838
www.carmix.xom/e-mail info@carmix.com

CARMIX 2.5 FX






One person likes this.







25 FX



**MIXING UNIT**: Drum capacity 3.450 liters. Concrete output: 2,5 m3 per batch. Double mixing screws, cover for emergency unloading. Mixing and discharging speed indipendent from r.p.m. of diesel engine. Discharging by reversing drum.



ENGINE: Perkins diesel engine 1104D-44T, water-cooled, 4 cylinders. Power KW 62,5 (84 HP) set at 2200 rpm.



**TRANSMISSION**: Hydrostatic Bosch-Rexroth. Heavy duty differential axles with planetary reducers. Front axle swinging and steering. Rear axke fixed.



## SPEED:

Working speed from 0 to 10 km/h, road transfer from 0 to 24 km/h.



#### **DRIVING SEAT:**

ROPS-FOPS canopy. Reversible seat with automatic inversion of hydraulic steering cicrcuit.



**HYDRAULIC SYSTEM**: three indipendent circuits. Two variable outlet pumps for hydrostatic transmission and drum rotation. One pump for services. Intlet and outlet filter. Heat exchanger water/oil-air type.



## **LOADING SHOVEL:**

Capacity 400 liters, complete with hydraulic opening gate.



## CHUTE:

Slewing and hydraulically tilting.



WATER SYSTEM: Self-contained. Hydraulic driven water pump, water meter, washing outlet.



#### **GRADIENT:**

Fully loaded 30%.

**BRAKES**: Oil bath disc brakes inside differential axles. Twin indipendent circuits.



Negative hydraulic parking brake.



## TYRES:

Off road industrial type 12.5-20 PR 12.



STEERING: Hydrostatic "load sensing". Radius: internal mm. 2550, external mm. 5100.



## **ELECTRIC SYSTEM:**

12 Volt. 120 Ah battery for electric starter and road lighting. Safety battery cut-off.



#### TANKS:

Water: 2x 275 liters. Diesel: 100 liters. Hydraulic oil: 70 liters.



## **CHASSIS:**

Steel profile specially engineered for off-road operations.



#### WEIGHT:

About Kg. 3.500, equally distributed on both axles



#### SAFETY:

Machine equipped with checking and block valves for maximum safety of the operator.



# **CATALOGUE:**

The machine is equipped with Use and Manteinance and Spare Parts manuals according to CE regulations.

OMOLOGAZIONE STRADALE: a carico secondo le leggi italiane.