



CARMIX by Metalgalante Srl

Via A. Volta 2 NOVENTA DI PIAVE

Venezia , VENETO 30020 ITALY

Tel : +39 0421 65191 / Fax : +39 0421 658838

www.carmix.com / e-mail info@carmix.com

CARMIX 2.5 TT



Like

4 people like this.



2.5 TT

MIXING UNIT: Drum capacity 3.450 liters. Concrete output: 2,5 m³ per batch. Double mixing screws, cover for emergency unloading. Drum rotation by hydraulic motor and planetary reducers. Mixing and discharging speed independent from r.p.m. of diesel engine. Discharging by reversing drum. The mixing unit is slewing hydraulically through 270° for high discharge over 1,9 m to the four sides of the vehicle.



ENGINE: Perkins diesel engine 1104D-44T, water-cooled, 4 cylinders. Rated power KW 62,5 (84 HP) set at 2.200 rpm. Engine mounted transversal on the rear.



TRANSMISSION: Hydrostatic Bosch Rexroth. Pump and motor are connected to the differentials through a 2 speed reducer (working and transfer). 4 wheel drive and steering.



SPEED:
Working speed from 0 to 9 km/h, road transfer from 0 to 25 km/h.



DRIVING SEAT:
Front cab on side of loading shovel. ROPS-FOPS type complete with double closing door.



HYDRAULIC SYSTEM: Three circuits. 2 variable outlet pumps for hydrostatic transmission and drum rotation. 2 gear pumps for services. Inlet and outlet filter. Heat exchanger water/oil-air type.



JOYMIX:
All hydraulic functions of shovel controlled by a single - fully servo controlled Joystick.



LOADING SHOVEL:
Capacity 400 liters, complete with hydraulic opening gate.



CHUTE:
Slewing and hydraulically tilting. Fitted with two pins easily detachable to increase the discharge height.



WATER SYSTEM: Self-contained. Hydraulic driven water pump, water meter. High pressure water pump (on request).



**GRADIENT:**

Fully loaded 30%.



BRAKES: Oil bath disc brakes inside differential axles. Twin independent circuits.

Negative hydraulic parking brake.

**TYRES:**

Off road industrial type 18-19,5 PR 16.



STEERING: Hydrostatic. 3 way steering. Radius: internal mm. 1500, external mm. 3500

**ELECTRIC SYSTEM:**

12 Volt. 120 Ah battery for electric starter and road lighting. Safety battery cut-off.

**TANKS:**

Water: 2x270 liters. Diesel: 105 liters. Hydraulic oil: 80 liters.

**CHASSIS:**

Steel profile specially engineered for off-road operations.

**WEIGHT:**

About Kg. 6.100, equally distributed on both axles

**SAFETY:**

Machine equipped with checking and block valves for maximum safety of the operator.

**CATALOGUE:**

The machine is equipped with Use and Maintenance and Spare Parts manuals according to CE regulations

OMOLOGAZIONE STRADALE: a carico secondo le leggi italiane.