



CARMIX by Metalgalante Srl

Via A. Volta 2 NOVENTA DI PIAVE

Venezia , VENETO 30020 ITALY

Tel : +39 0421 65191 / Fax : +39 0421 658838


www.carmix.com / e-mail info@carmix.com

CARMIX DUMPER D6



Like

Be the first of your friends to like this.



D6



LOADING CAPACITY:

Struck: 4500 liters. Heaped: 6000 litri.



ENGINE: Diesel Perkins 1104 D-44 TA Turbo water-cooled, 4 cylinders.

Maximum power 83 kW (111 HP), set at 2200 r.p.m.



TRANSMISSION: fully hydrostatic Bosch Rexroth with electric inverter.

Gear box with mechanic control, two speeds. 4 wheel drive.



SPEED: Working speed from 0 to 9 km/h.

Road transfer from 0 to 25 km/h.



DRIVING SEAT: Reversible seat with automatic inversion of hydraulic steering circuits.

ROPS-FOPS cab closed on 3 sides.



HYDRAULIC SYSTEM: 2 independent circuits, variable outlet pump for hydrostatic transmission and hydraulic pump for services. Heat exchanger water-oil-air/air type.



BUCKET: Heavy duty rock type. Hydraulic tilting with 2 cylinders.



AXLES: Dana Spicer with oil bath disc brakes and planetary reducers. Front axle steering and swinging. Rear axle fixed



GRADIENT: fully loaded 30%



BRAKES: Oil bath disc brakes on 4 wheels.

Hydraulic parking brake negative on rear axle manually operated.



TYRES:

Off road industrial type 16/70-20 14 PR.



STEERING: Hydrostatic, "load sensing" type.

Radius: internal 2900 mm. external 5800 mm.



ELECTRIC SYSTEM: 12 volt. 120 Ah battery for electric starter and road lighting.

Safety battery cut-off.



TANKS: Diesel: 115 liters. Hydraulic oil: 80 litri.



CHASSIS: Steel profile specially engineered for off-road operations.



WEIGHT: Empty: 5800 kg equally distributed on both axles.

PAYLOAD: Kg. 10.000.



SAFETY:

Machine equipped with checking and block valves for maximum safety of the operator.



CATALOGUES:

The machine is equipped with Use and Maintenance and Spare Parts Manuals according to CE regulations.

OMOLOGAZIONE STRADALE: a carico secondo le leggi italiane.